

DH-SD6CE232GB-HNR

2MP 32x Starlight IR WizSense Network PTZ Camera



WizSense

Launched by Dahua Technology, WizSense is a series of AI products and solutions that adopt independent AI chip and deep learning algorithm. It focuses on human and vehicle with high accuracy, enabling users to fast act on defined targets. Based on Dahua's advanced technologies, WizSense provides intelligent, simple and inclusive products and solutions.

System Overview

With its powerful optical zoom, and accurate pan and tilt capabilities, the PTZ camera provides an all-in-one solution for long distance video surveillance of outdoor scenes. Together with infrared illumination and Starlight Technology, the camera is a great solution for dark, low light conditions. The series combines a day and night mechanical IR cut filter to produce high quality images in variable lighting conditions during the day.

Functions

Perimeter Protection

Automatically filters out false alarms caused by animals, rustling leaves, bright lights, and more, and uses secondary recognition during target detection to improve alarm accuracy.

Face Detection

Supports 6 attributes and 8 expressions: Gender, age, glasses, face mask, beard and expressions (anger, sadness, disgust, fear, surprise, calm, happiness, and confusion). It also supports face cutout settings: Face, and single inch photo. Three snapshot methods are also featured: Real-time snapshot, priority snapshot, and quality priority.

Wide Dynamic Range

The camera produces vivid images, even in high-contrast lighting conditions, by using industry-leading wide dynamic range (WDR) technology. For scenes that quickly alternate between bright and low lighting, WDR adjusts to fully capture both the bright and dark areas of a scene, producing superior quality videos.

- 1/2.8" 2Megapixel STARVIS™ CMOS.
- 32× optical zoom.
- Starlight technology.
- Max. 50/60 fps@1080p.
- IR distance up to 250 m.
- Auto Tracking 3.0.
- Perimeter protection.
- Face detection.
- SMD 4.0
- IP67, IK10.



Starlight Technology

For challenging low-light conditions, Dahua's Starlight Ultra-low Light Technology offers the best in light sensitivity, capturing color in vivid detail, even in lighting as low as 0.005 lux. The camera uses a set of optical features to balance light throughout the scene, producing clear images in dark environments.

SMD 4.0

Dahua Smart Motion Detection technology works with intelligent algorithms to classify targets that trigger motion detection alarms. It filters out objects that are not targets, such as small and large animals, to avoid triggering false alarms. With an AI NVR, Quick Pick technology becomes available, allowing you to easily search for and pick out human and vehicle targets from SMD event videos, prioritizing the highest matches.

Protection (IP67, TVS 8000 V)

IP67, TVS 8000 V lightning proof, surge protection, and voltage transient protection.

Environment (−40 °C to +70 °C, IP67)

Developed to operate in extreme conditions, Dahua camera can function in temperatures ranging from −40 °C to +70 °C (−40 °F to +158 °F) at 95% humidity. It was subjected to rigorous dust and water immersion tests, gaining its IP67 Ingress Protection certification, making it suitable for demanding outdoor applications.

Auto-tracking

This feature controls the pan/tilt/zoom actions of the camera to automatically track an object in motion and to keep it in the scene. The tracking action can be triggered manually or automatically by defined rules. Once a rule is triggered, the camera can zoom in and track the defined target automatically.

Technical Specification

Camera

| | |
|----------------------------|---|
| Image Sensor | 1/2.8" CMOS |
| Pixel | 2 MP |
| Max. Resolution | 1920 (H) × 1080 (V) |
| ROM | 4 GB |
| RAM | 1 GB |
| Electronic Shutter Speed | 1/1 s–1/30,000 s |
| Scanning System | Progressive |
| Min. Illumination | Color: 0.005 lux@F1.6 B/W: 0.0005 lux@F1.6 0 lux@F1.6 (IR light on) |
| Illumination Distance | 250 m (820.21 ft) (IR) |
| Illuminator On/Off Control | Zoom Prio; Manual; Smart IR; Off |
| Illuminator Number | 6 (IR) |

Lens

| | | | | |
|----------------------|---|------------------------|------------------------|----------------------|
| Focal Length | 4.8 mm–154 mm | | | |
| Max. Aperture | F1.6–F4.0 | | | |
| Field of View | H: 60.2°–2.7°; V: 34°–1.5°; D: 68°–3° | | | |
| Optical Zoom | 32× | | | |
| Focus Control | Auto; semi-auto; manual | | | |
| Close Focus Distance | 0.8 m–5.0 m (2.62 ft–16.40 ft) | | | |
| Iris Control | Auto; manual | | | |
| DORI Distance | Detect | Observe | Recognize | Identify |
| | 1,986 m (6,915.75 ft) | 785 m (2,575.46 ft) | 398 m (1,305.77 ft) | 198 m (649.61 ft) |
| | *DORI (Detect, Observe, Recognize, Identify) is a standard system (EN-62676-4) for defining the ability of a person viewing the video to distinguish persons or objects within a covered area. The numbers in this table do not reflect intelligent function distances. For intelligent function distances, refer to installation and commissioning manual/project design tool. | | | |

PTZ

| | |
|----------------------|---|
| Pan/Tilt Range | Pan: 0° to 360° endless Tilt: –20° to +90°, auto flip 180° |
| Manual Control Speed | Pan: 0.1°/s–260°/s Tilt: 0.1°/s–120°/s |
| Preset Speed | Pan: 0°/s–300°/s Tilt: 0°/s–200°/s |
| Preset | 300 |
| Tour | 8 (up to 32 presets per tour) |
| Pattern | 5 |
| Scan | 5 |
| Power-off Memory | Yes |
| Idle Motion | Pattern; Preset; Scan; Tour |

PTZ Protocol

| |
|--------------------------------------|
| DH-SD Pelco-P/D(Auto recognition) |
|--------------------------------------|

Intelligence

| | |
|-----------------------------------|--|
| Video Metadata | Detects motor and non-motor vehicles, faces and human bodies. It also performs tracking, takes snapshots, uploads high-quality face images and optimizes images. It extracts attributes from motor vehicles, detecting up to 10 attributes for them |
| IVS (Perimeter Protection) | Tripwire; intrusion; crossing fence detection; loitering detection; abandoned/missing object; fast moving; parking detection; people gathering; Vehicle/Human Alarm Classification; linkage tracking |
| Face Detection | Face detection; bounding box; optimization; capturing pictures; uploading high-quality face snapshots; face enhancement. Face attributes: Gender, age, facial expressions (Anger, sad, antipathy, fear, surprise, calm, happy, and confused), face mask, and mustache. Face image and 1 inch photos are supported for face cutouts. Face capture: Real-time snapshot, face priority, and quality priority |
| Construction Detection | Detects 6 helmet colors: Red, orange, yellow, blue, white, and black. An alarm will be triggered when a person is not wearing a helmet or when the color of the helmet that they are wearing does not match the configured color. It also supports compliance detection for work uniforms. Up to 5 work uniform sample libraries can be uploaded, which together can contain up to 1,000 images (the images must be 1080p and in the JPG format). An alarm will be triggered when the similarity between the detected work uniform and the samples in the library is below the set threshold (that is, below the minimum compliance standard for work uniforms). The system supports detecting the attributes of work uniforms such as the color of the uniform, and whether or not the person is wearing a mask and wearing shoe covers. An alarm will be triggered when the target is detected as not meeting the set requirements. It also detects and triggers alarms when only one person is in the construction site, and when no one is present in the detection area such as when a worker leaves their post or an area is left unmanned |
| Auto Tracking | Yes |
| SMD | SMD 4.0 |
| Acupick | Uses deep learning algorithms and works with back-end devices to accurately match targets, such as people and motor vehicles, and search through live and recorded videos to quickly locate targets |
| Auto Patrol | It triggers the IVS rule when a target is detected and makes the camera link with the PTZ to rotate to the position of the target and patrol based on its presets |

Video

| | |
|-----------------------------|--|
| Video Compression | H.264H; H.264B; Smart H.265+; H.264; H.265; MJPEG (Sub Stream); Smart H.264+ |
| Streaming Capability | 3 streams |
| Resolution | 1080p(1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240) |
| Video Frame Rate | Main stream: 1080p/1.3M/720p@(1–50/60 fps) Sub stream 1: D1/VGA/CIF@ (1–25/30 fps) Sub stream 2: 1080p/1.3M/720p @ (1–25/30 fps) |
| Bit Rate Control | CBR/VBR |
| Video Bit Rate | H264: 64 Kbps–10496 Kbps H265: 25 Kbps–6400 Kbps |
| Day/Night | Auto (ICR)/Color/B/W |

| | |
|--------------------------|--|
| BLC | Yes |
| WDR | 120 dB |
| HLC | Yes |
| White Balance | Auto; indoor; outdoor; tracking; manual; sodium lamp; natural light; street lamp |
| Gain Control | Auto; manual |
| Noise Reduction | 2D NR; 3D NR |
| Motion Detection | Yes |
| Region of Interest (RoI) | Yes |
| Image Stabilization | Yes |
| Defog | Electronic |
| Digital Zoom | 16x |
| Image Rotation | 180° |
| Privacy Masking | Up to 24 areas can be set, with up to 8 areas in the same view. |
| S/N Ratio | ≥ 55 dB |

Audio

| | |
|-------------------|---|
| Audio Compression | PCM; G.711a; G.711Mu; G.726; MPEG2-Layer2; G722.1; G729; G723 |
|-------------------|---|

Network

| | |
|---------------------|--|
| Network Port | 1xRJ-45 (10/100 Base-T) |
| Network Protocol | FTP; RTMP; IPv6; Bonjour; IPv4; DNS; RTCP; PPPoE; NTP; RTP; 802.1x; HTTPS; SNMP; TCP/IP; DDNS; UPnP; NFS; ICMP; UDP; IGMP; HTTP; SSL; DHCP; SMTP; Qos; RTSP; ARP |
| Interoperability | CGI; SDK; ONVIF (Profile S&G&T&M) |
| Streaming Method | Unicast/Multicast |
| User/Host | 20 (total bandwidth: 64 M) |
| Storage | Micro SD card (Max 512 GB); FTP/SFTP; NAS |
| Browser | IE 9 and later versions Chrome 42 and later versions Firefox 50 and later versions Safari 10 and later versions |
| Management Software | DSS; DMSS; Easy4ip; Smart PSS; IVSS |
| Mobile Client | iOS; Android |

Certification

| | |
|----------------|--|
| Certifications | CE: EN55032/EN55024/EN50130-4 FCC: Part15 subpartB, ANSI C63.4- 2014 |
|----------------|--|

Port

| | |
|---------------|---|
| Analog Output | 1 channel (CVBS output, BNC) |
| RS-485 | 1 (baud rate: 1200 bps–9600 bps) |
| Audio Input | 1 channel (LINE IN, bare wire) |
| Audio Output | 1 channel (LINE OUT, bare wire) |
| Alarm Linkage | Capture; preset; tour; pattern; recording; alarm digital input; audio; send email |

| | |
|-------------|---|
| Alarm Event | Motion/tampering detection; audio detection; network disconnection detection; IP conflict detection; memory card state detection; memory space detection; power exception detection |
| Alarm I/O | 7/2 |
| Audio I/O | 1/1 |

Power

| | |
|-------------------|---|
| Power Supply | 24 VDC, 2.5 A ± 25%, PoE+ (802.3at) |
| Power Consumption | Max.: 25.5 W (illuminator + heater + PTZ) |

Environment

| | |
|-----------------------|---|
| Operating Temperature | -40 °C to +70 °C (-40 °F to +158 °F) |
| Operating Humidity | ≤ 95% |
| Protection | IP67; IK10; TVS 8000V lightning proof; surge protection; voltage transient protection |

Structure

| | |
|--------------------|--------------------------------------|
| Product Dimensions | 337.4 mm × Ø209 mm (13.28" × Ø8.23") |
| Net Weight | 5.8 kg (12.79 lb) |
| Gross Weight | 9.4 kg (20.72 lb) |

Ordering Information

| Type | Model | Description |
|---------------------------------|-------------------|--|
| 2MP WizSense Network PTZ Camera | DH-SD6CE232GB-HNR | 2MP 32x Starlight IR WizSense Network PTZ Camera |
| | SD6CE232GB-HNR | 2MP 32x Starlight IR WizSense Network PTZ Camera |
| Accessories | DC24V/2.5A | Power Adapter |
| | PFB305W | Wall Mount Bracket |
| | PFA111 | Mount Adapter |
| | PFA140 | Power Box |
| | PFB300C | Ceiling Mount Bracket |
| | PFA120 | Juncton Box |
| | PFA150 | Pole Mount Bracket |
| | PFA151 | Corner Mount Bracket |
| | PFB303S | Parapet Mount Bracket |

Accessories

Included:



DC24V/2.5A
Power Adapter



PFB305W
Wall Mount Bracket

Optional:



PFA111
Mount
Adapter



PFA140
Power
Box



PFB300C
Ceiling Mount
Bracket



PFA120
Juncton
Box



PFA150
Pole Mount
Bracket




PFA151
Corner Mount
Bracket



PFB303S
Parapet Mount
Bracket

Dimensions (mm[inch])



| Wall Mount | Ceiling Mount | Ceiling Mount |
|----------------------|----------------|------------------------|
| PFB305W+PFA120 | PFA111+PFB300C | PFA111+PFB301C |
| | | |
| Pole Mount(Vertical) | Corner Mount | Pole Mount(Horizontal) |
| PFB305W+PFA150 | PFB305W+PFA151 | PFA111+PFB300C+PFA150 |
| | | |
| Plane Mount | Parapet Mount | |
| PFB301S-E | PFA111+PFB303S | |
| | | |

Rev 002.000 © 2025 Dahua. All rights reserved. Design and specifications are subject to change without notice. The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product.